

Contents

Abstract	i
1. Introduction	1
1.1. The global laser market	2
1.2. State of the art	3
1.3. Structure of this work	6
2. Theoretical Background	7
2.1. Concept and physics of broad-area laser bars	7
2.2. Definition and governing effects of beam quality in broad-area lasers	10
2.3. Strained diode-laser chips	14
2.4. Thermal aspects of diode-laser operation	18
3. Experimental Methods	21
3.1. Fabrication of broad-area laser bars	21
3.2. Characterization techniques	23
3.2.1. Determination of internal laser parameters	24
3.2.2. Electro-optical characterization and spectra	25
3.2.3. Test station for the analysis of bar beam-quality	26
3.2.4. Measurement of bar smile	39
4. Diode-Laser Bars for Highly Efficient 1 kW-Emission	41
4.1. Vertical structure for high-efficiency operation	41
4.2. Thermal transient	44
4.3. Varied resonator length	48
4.4. Impact of the lateral design	52
4.5. Conclusions	57
5. Efficient 1 kW-Emitting Bars Exhibiting Narrow Far Field	61
5.1. Mechanical chip deformation (bar smile)	61
5.2. Emitter cross heating	69
5.3. Bar edge emitters	73
5.4. Emitter sub-structure	78
5.5. Conclusions	81

6. Conclusions and Outlook	87
Appendices	95
A. Beam-Path Calculation Using the Matrix Formalism	95
B. Thermal Wavelength Dependence of Longitudinal Modes	97
Bibliography	98
Public Contributions	108
Acknowledgements	109
Biographical Sketch	110